

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.02.2013



Version number 1



Revision: 06.02.2013

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** edding 5200 permanent spray premium acrylic lacquer
- **1.2 Relevant identified uses of the substance or mixture and uses advised against --**
- **Application of the substance / the preparation** Lacquer
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
edding International GmbH
Bookkoppel 7
D-22926 Ahrensburg
phone +49 (0) 41 02 80 8-0
e-Mail: zentrale@edding.de
- **Further information obtainable from:** +49 (0) 41 02 80 8-0
- **1.4 Emergency telephone number:**
For medical advice (advice in German and English)
+49 (0) 30 30686 790 (Poison Centre Berlin)

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
-  Xi; Irritant
- R36: Irritating to eyes.
-  F+; Extremely flammable
- R12: Extremely flammable.
- R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.
- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
Warning! Pressurized container.
Has a narcotizing effect.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **2.2 Label elements**
- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
-   Xi Irritant
F+ Extremely flammable
- **Risk phrases:**
12 Extremely flammable.
36 Irritating to eyes.
66 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.02.2013

Version number 1

Revision: 06.02.2013

Trade name: edding 5200 permanent spray premium acrylic lacquer

(Contd. of page 1)

67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

2 Keep out of the reach of children.

16 Keep away from sources of ignition - No smoking.

23 Do not breathe spray.

24/25 Avoid contact with skin and eyes.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C (e.g. in the car). Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Buildup of explosive mixtures possible without sufficient ventilation.

· **Classification in accordance with Directive 75/324/EEC: Extremely flammable**· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **3.2 Chemical characterization: Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

| | | |
|---|---|-----------|
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29 | n-butyl acetate R10-66-67 ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336 | 25-<50% |
| CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 02-2119752542-40 01-2119471330-49 | acetone ☒ Xi R36; 🔥 F R11 R66-67 ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 | 12.5-<20% |
| CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37 | dimethyl ether 🔥 F+ R12 ⚠ Flam. Gas 1, H220; Press. Gas, H280 | 12.5-<20% |
| CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21 | propane 🔥 F+ R12 ⚠ Flam. Gas 1, H220; Press. Gas, H280 | 5-<10% |
| CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32 | butane 🔥 F+ R12 ⚠ Flam. Gas 1, H220; Press. Gas, H280 | 5-<10% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 02-2119752448-30-0000 01-2119486136-34-xxxx 05-2116469897-19-0000 01-2119488216-32 | xylene, mixture of isomers ☒ Xn R20/21; ☒ Xi R38 R10 ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | 2.5-<5.0% |

(Contd. on page 3)

GB

Safety data sheet
according to 1907/2006/EC, Article 31


























Printing date 06.02.2013

Version number 1

Revision: 06.02.2013

Trade name: edding 5200 permanent spray premium acrylic lacquer

(Contd. of page 2)

| | | |
|---|---|-------|
| CAS: 75-28-5 EINECS: 200-857-2 | isobutane  F+ R12  Flam. Gas 1, H220; Press. Gas, H280 | <2.5% |
| CAS: 64742-94-5 EINECS: 265-198-5 Reg.nr.: 01-2119463583-34 | Solvent naphtha (petroleum), heavy arom.  Xn R65 R52/53-66-67  Asp. Tox. 1, H304 | <2.5% |
| CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 | 2-methoxy-1-methylethyl acetate R10  Flam. Liq. 3, H226 | <2.5% |
| CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 02-2119752543-38 01-2119457558-25 | propan-2-ol  Xi R36;  F R11 R67  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336 | <2.5% |
| CAS: 108-67-8 EINECS: 203-604-4 | mesitylene  Xi R37;  N R51/53 R10  Flam. Liq. 3, H226;  Aquatic Chronic 2, H411;  STOT SE 3, H335 | ≤0.5% |
| CAS: 103-65-1 EINECS: 203-132-9 | propylbenzene  Xn R65;  Xi R37;  N R51/53 R10  Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  STOT SE 3, H335 | ≤0.5% |
| CAS: 64742-82-1 EINECS: 265-185-4 Reg.nr.: 01-2119458049-33 01-2119463586-28 | Naphtha (petroleum), hydrodesulfurized heavy  Xn R65;  N R51/53 R10-66-67  Flam. Liq. 3, H226;  Asp. Tox. 1, H304 | ≤0.5% |

Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply.

For the wording of the listed risk phrases refer to section 16.

4 First aid measures**4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures**5.1 Extinguishing media**

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**

Water

Water with full jet

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters -**

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.02.2013

Version number 1

Revision: 06.02.2013

Trade name: edding 5200 permanent spray premium acrylic lacquer

(Contd. of page 3)

· **Protective equipment:** No special measures required.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Do not allow product to reach sewage system or any water course.

· 6.3 Methods and material for containment and cleaning up:

Do not flush with water or aqueous cleansing agents

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Storage class: 2B

· 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL () Short-term value: 966 mg/m³, 200 ppmLong-term value: 724 mg/m³, 150 ppm

67-64-1 acetone

WEL () Short-term value: 3620 mg/m³, 1500 ppmLong-term value: 1210 mg/m³, 500 ppm

115-10-6 dimethyl ether

WEL () Short-term value: 958 mg/m³, 500 ppmLong-term value: 766 mg/m³, 400 ppm

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.02.2013

Version number 1

Revision: 06.02.2013

Trade name: edding 5200 permanent spray premium acrylic lacquer

(Contd. of page 4)

106-97-8 butane

WEL () Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

1330-20-7 xylene, mixture of isomers

WEL () Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

108-65-6 2-methoxy-1-methylethyl acetate

WEL () Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

67-63-0 propan-2-ol

WEL () Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

· Ingredients with biological limit values:**1330-20-7 xylene, mixture of isomers**

BMGV () 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

-
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.
Otherwise, filter class A / P2 or self contained.

· Protection of hands:

Protective gloves

Solvent resistant gloves

In case of contact with spray dust protective gloves made of butyl should be used (min. 0.4 mm thick), e.g. KCL Camatril, article no. 898 or similar products

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Butyl rubber, BR**· Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.02.2013

Version number 1

Revision: 06.02.2013

Trade name: edding 5200 permanent spray premium acrylic lacquer

(Contd. of page 5)

· **Eye protection:** Safety glasses

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

| | |
|---------------------------|------------------------------------|
| · Form: | Aerosol |
| · Colour: | According to product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |

| | |
|--------------------|-----------------|
| · pH-value: | Not determined. |
|--------------------|-----------------|

· Change in condition

| | |
|---------------------------------------|-----------------------------|
| · Melting point/Melting range: | Undetermined. |
| · Boiling point/Boiling range: | Not applicable, as aerosol. |

| | |
|-----------------------|-----------------------------|
| · Flash point: | Not applicable, as aerosol. |
|-----------------------|-----------------------------|

| | |
|---|-----------------|
| · Flammability (solid, gaseous): | Not applicable. |
|---|-----------------|

| | |
|-------------------------------------|-----------------|
| · Decomposition temperature: | Not determined. |
|-------------------------------------|-----------------|

| | |
|-------------------------|------------------------------|
| · Self-igniting: | Product is not selfigniting. |
|-------------------------|------------------------------|

| | |
|-------------------------------|--|
| · Danger of explosion: | In use, may form flammable/explosive vapour-air mixture. |
|-------------------------------|--|

· Explosion limits:

| | |
|-----------------|------------|
| · Lower: | 1.2 Vol % |
| · Upper: | 18.6 Vol % |

| | |
|------------------------------------|----------|
| · Vapour pressure at 20 °C: | 5200 hPa |
|------------------------------------|----------|

| | |
|----------------------------|------------------------|
| · Density at 20 °C: | 0.86 g/cm ³ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not applicable. |

| | |
|--|-----------------------------------|
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
|--|-----------------------------------|

| | |
|---|-----------------|
| · Partition coefficient (n-octanol/water): | Not determined. |
|---|-----------------|

· Viscosity:

| | |
|---------------------|-----------------|
| · Dynamic: | Not determined. |
| · Kinematic: | Not determined. |

· Solvent content:

| | |
|-------------------|-----------|
| · VOC-(EU) | --- |
| | 711.5 g/l |

| | |
|--------------------------------|--|
| · 9.2 Other information | No further relevant information available. |
|--------------------------------|--|

10 Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.02.2013

Version number 1

Revision: 06.02.2013

Trade name: edding 5200 permanent spray premium acrylic lacquer

(Contd. of page 6)

· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **11.1 Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values relevant for classification:****67-64-1 acetone**

Oral LD50 5800 mg/kg (rat)

Dermal LD50 20000 mg/kg (rabbit)

· **Primary irritant effect:**· **on the skin:** No irritant effect.· **on the eye:** Irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Vapours have narcotic effect.

12 Ecological information

· **12.1 Toxicity**· **Aquatic toxicity:** No further relevant information available.· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **Additional ecological information:**· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 04 metallic packaging

15 01 11* metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.02.2013



Version number 1

Revision: 06.02.2013

Trade name: edding 5200 permanent spray premium acrylic lacquer

(Contd. of page 7)

14 Transport information

| | |
|---|--|
| · 14.1 UN-Number · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name · ADR · IMDG · IATA | 1950 AEROSOLS AEROSOLS AEROSOLS, flammable |
| · 14.3 Transport hazard class(es) · ADR | |
|  | |
| · Class · Label | 2 5F Gases. 2.1 |
| · IMDG, IATA | |
|  | |
| · Class · Label | 2.1 2.1 |
| · 14.4 Packing group · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: · Marine pollutant: | No |
| · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: | Warning: Gases. - F-D,S-U |
| · 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code | 1L 2 D |

15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H220 Extremely flammable gas.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.02.2013

Version number 1

Revision: 06.02.2013

Trade name: edding 5200 permanent spray premium acrylic lacquer

(Contd. of page 8)

- H225 *Highly flammable liquid and vapour.*
H226 *Flammable liquid and vapour.*
H280 *Contains gas under pressure; may explode if heated.*
H304 *May be fatal if swallowed and enters airways.*
H312 *Harmful in contact with skin.*
H315 *Causes skin irritation.*
H319 *Causes serious eye irritation.*
H332 *Harmful if inhaled.*
H335 *May cause respiratory irritation.*
H336 *May cause drowsiness or dizziness.*
H411 *Toxic to aquatic life with long lasting effects.*
- R10 *Flammable.*
R11 *Highly flammable.*
R12 *Extremely flammable.*
R20/21 *Harmful by inhalation and in contact with skin.*
R36 *Irritating to eyes.*
R37 *Irritating to respiratory system.*
R38 *Irritating to skin.*
R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
R52/53 *Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
R65 *Harmfull: may cause lung damage if swallowed*
R66 *Repeated exposure may cause skin dryness or cracking.*
R67 *Vapours may cause drowsiness and dizziness.*

· **Contact:** Produktentwicklung

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent